

# Green Pin® Closed Sockets G-6411



## spelter type

**Material:** High tensile steel  
**Finish:** Hot dipped galvanised  
**Temp Range:** Minus 20°C up to 200°C  
**Certificate:** This product is supplied with an EC declaration of conformity upon request a proof load certificate

No.	MBL	dia wire rope	length	width	width inside bow	length inside bow	dia bow	openin bow	product code	weight each	
	tons	mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg	
296	8	6 - 7	101	37	22	40	11	13	8.5	53999	0.30
297	12	8 - 10	119	43	25	48	14	17.5	12	54000	0.50
298	20	11 - 13	140	52	30	58	18	23.4	14.8	54001	0.70
299	25	14 - 16	162	68	37	66	21	26	17.6	54002	1.50
200	40	18 - 19	194	76	42	78	27	32	21.5	54003	2.10
201	55	20 - 22	224	92	47	90	33	38	24	54004	3.60
204	75	23 - 26	253	104	57	103	36	44	28	54005	5.80
207	90	27 - 30	282	114	63	116	39	51	32	54006	7.00
212	125	31 - 36	312	127	70	130	43	57	38	54007	10.50
215	150	37 - 39	358	136	79	155	51	63	41	54008	13.00
217	170	40 - 42	390	146	83	171	54	70	44	54009	17.00
219	225	43 - 48	443	171	93	198	55	76	51	54010	26.00
222	280	49 - 54	502	193	100	224	62	82	57	54011	37.50
224	360	55 - 60	548	216	112	247	73	92	63	54012	50.00
226	425	61 - 68	597	241	140	270	79	102	73	54013	65.00
227	460	69 - 75	644	273	159	286	79	124	79	54014	94.00
228	560	76 - 80	686	292	171	298	83	133	86	54015	115.00
229	625	81 - 86	743	311	184	311	102	146	92	54016	145.00
230	720	87 - 93	788	330	197	330	102	159	99	54017	168.00
231	875	94 - 102	845	362	216	356	108	178	108	51018	210.00
233	1200	108 - 115	1000	405	235	425	125	190	125	54019	330.00
240	1300	120 - 130	1150	450	260	525	125	200	143	54020	500.00

