

Thimbles

solid type

Material: Malleable cast iron
Standard: B.S. 464 table 3 - 1958
Finish: Self colour, hot dipped galvanised available - price on request
Note: As standard the castings are supplied unmachined, for the B.S. 464 standard to apply, thimbles require machining both sides
Note: Prices for drilled and/or machined finish are available on request



diameter rope	width overall	width outside *	width inside	length overall	maximum hole permitted	product code	weight each
a inch	b inch	c inch	d inch	e inch	** inch		kg
5/16	1.3/8	7/16	1	1.7/8	1/2	44001	0.09
3/8	1.3/4	9/16	1.1/4	2.1/4	5/8	44002	0.17
7/16	2.1/16	11/16	1.1/2	2.3/4	3/4	44003	0.30
1/2	2.3/8	13/16	1.3/4	3.1/4	7/8	44004	0.39
5/8	2.3/4	7/8	2	3.3/4	1	44005	0.60
3/4	3.3/8	1.1/8	2.1/2	4.5/8	1.1/4	44006	1.19
7/8	3.3/4	1.1/4	2.3/4	5	1.3/8	44007	1.57
15/16	4.1/8	1.5/16	3	5.1/2	1.1/2	44008	1.73
1	4.1/2	1.7/16	3.1/4	6	1.5/8	44009	2.43
1.1/8	4.7/8	1.9/16	3.1/2	6.1/2	1.3/4	44010	3.12
1.1/4	5.1/2	1.3/4	4	7.1/2	2	44011	4.40
1.3/8	6.1/8	2	4.1/2	8.1/4	2.1/4	44012	6.32
1.1/2	6.3/4	2.1/4	5	9.1/4	2.1/2	44013	9.20

* Dimension shown as C - width outside is the finished size after machining both sides and not the size of the casting offered as standard

** The maximum pin hole size permitted in the standard

