

# Dynamo Eyebolts

## BSW thread

- Material:** BS970-080A27 normalised  
**Safety Factor:** MBL equals 5 x SWL  
**Finish:** Self colour  
**Certificate:** This product is supplied with an EC declaration of conformity, upon request a certificate of basic raw material  
**Note:** Electro galvanised (zinc plated) also available - prices on request  
**Special Note:** These eyebolts are for a vertical lift only

safe working load	diameter thread	diameter eye inside	diameter eye	length base to centre	length thread	base height	diameter base	product code	weight each
tonnes	a inch	b inch	c inch	d inch	e inch	f inch	g inch		kg
0.10	1/4	7/8	3/8	1.1/16	3/4	1/4	3/4	22501A	0.08
0.15	5/16	7/8	3/8	1.1/16	3/4	1/4	3/4	22502A	0.09
0.25	3/8	7/8	3/8	1.1/16	3/4	1/4	3/4	22503A	0.09
0.50	1/2	1.1/16	7/16	1.3/8	1	5/16	1	22505A	0.14
0.80	5/8	1.1/4	1/2	1.5/8	1.1/8	3/8	1.1/8	22507A	0.24
1.20	3/4	1.9/16	11/16	2.1/8	1.1/4	3/8	1.7/16	22508A	0.43
1.60	7/8	1.3/4	11/16	2.5/16	1.3/8	3/8	1.3/8	22509A	0.61
2.20	1	2	13/16	2.7/16	1.13/16	1/2	1.5/8	22510A	0.88
2.65	1.1/8	2.3/8	1	2.7/8	2.1/16	3/4	2.1/8	22511A	1.63
3.50	1.1/4	2.3/8	1	2.7/8	2.1/16	3/4	2.1/8	22512A	1.70

