

Small Bow Shackles - Quality Range

with type A screw collar pin



Material: Body and pin high tensile steel
Safety Factor: MBL equals 5 x WLL
Standard: B.S.3032 table 4 - 1958
Finish: Hot dipped galvanised
Certificate: As standard an EC declaration of conformity is supplied, also upon request a certificate of basic raw material

| Working Load Limit | diameter bow | diameter pin | diameter eye | inside width | inside length | width bow | product code | weight each |
|--------------------|--------------|--------------|--------------|--------------|---------------|-----------|--------------|-------------|
| tons | a inch | b inch | c inch | d inch | e inch | f inch | | kg |
| 0.50 | 3/8 | 1/2 | 1 | 5/8 | 1.1/2 | 7/8 | 11401A | 0.18 |
| 1.00 | 1/2 | 5/8 | 1.1/4 | 7/8 | 2 | 1.1/8 | 11402A | 0.34 |
| 1.50 | 5/8 | 3/4 | 1.1/2 | 1.1/8 | 2.1/2 | 1.1/2 | 11403A | 0.62 |
| 2.00 | 3/4 | 7/8 | 1.3/4 | 1.3/8 | 3 | 1.3/4 | 11404A | 1.05 |
| 3.00 | 7/8 | 1 | 2 | 1.1/2 | 3.1/2 | 2 | 11405A | 1.63 |
| 4.00 | 1 | 1.1/8 | 2.1/4 | 1.3/4 | 4 | 2.3/8 | 11406A | 2.28 |
| 5.00 | 1.1/8 | 1.1/4 | 2.1/2 | 2 | 4.1/2 | 2.5/8 | 11407A | 3.20 |
| 6.25 | 1.1/4 | 1.3/8 | 2.3/4 | 2.1/4 | 5 | 3 | 11408A | 4.54 |
| 7.50 | 1.3/8 | 1.1/2 | 3 | 2.3/8 | 5.1/2 | 3.1/4 | 11409A | 5.74 |
| 9.25 | 1.1/2 | 1.3/4 | 3.1/2 | 3.5/8 | 6 | 3.1/2 | 11410A | 8.51 |
| 10.50 | 1.5/8 | 1.7/8 | 3.3/4 | 2.7/8 | 6.1/2 | 3.7/8 | 11411A | 11.23 |
| 12.50 | 1.3/4 | 2 | 4 | 3.1/8 | 7 | 4.1/8 | 11412A | 13.47 |

