

Open Sockets

British standard

Material: Body and pin high tensile steel
Standard: B.S. 463 - 1958 - part 1
Safety Factor: MBL equals 5 x SWL
Finish: Self colour
Certificate: This product is supplied with an EC declaration of conformity
Tolerances: Please refer to B.S. 1718 as specified in B.S.463 (drop forged allowances)
Note: Dimension B shown can only be achieved if the basket is machined,
 For tolerances please consult our technical department
Note: Hot dipped galvanised also available - prices on request

safe working load	dia wire rope	length basket	width inside	dia pin	length inside to pin centre	opening	product code	weight each
tons	inch	a inch	b inch	c inch	d inch	e inch		kg
0.50	1/4	1.11/16	5/8	1/2	1.1/4	5/16	51001	0.34
0.75	5/16	1.11/16	5/8	1/2	1.1/4	3/8	51002	0.34
1.00	3/8	2	7/8	5/8	1.11/16	15/32	51003	0.57
1.25	7/16	2	7/8	5/8	1.11/16	17/32	51004	0.57
2.00	1/2	2.3/8	1.1/8	13/16	2.1/16	19/32	51005	0.80
2.25	9/16	2.3/8	1.1/8	13/16	2.1/16	21/32	51006	0.80
3.00	5/8	2.3/4	1.1/4	15/16	2.1/2	23/32	51007	1.14
4.25	3/4	3	1.1/2	1.1/8	2.5/8	27/32	51008	1.93
5.50	7/8	3.3/8	1.11/16	1.1/4	3	1	51009	2.73
7.50	1	4.1/8	1.7/8	1.1/2	3.1/2	1.1/8	51010	4.77
9.50	1.1/8	4.1/2	2	1.5/8	4	1.1/4	51011	6.82
11.50	1.1/4	5.1/4	2.1/8	1.7/8	4.3/8	1.3/8	51012	10.00
14.00	1.3/8	6	2.9/16	2.1/4	4.1/2	1.9/16	51013	15.23
16.50	1.1/2	6	2.9/16	2.1/4	4.1/2	1.11/16	51014	15.23
19.00	1.5/8	6	2.9/16	2.1/4	4.1/2	1.13/16	51015	15.23
25.00	2	7.11/16	3.1/8	2.3/4	6.1/2	2.13/16	51017	56.00
38.00	2.1/4	9	3.3/4	3.1/2	7.1/2	2.1/2	51018	64.00

