

Green Pin® Trawling Dee Shackles G-4154

with square headed screw pin

Material: Bow and pin high tensile steel, Grade 6, quenched and tempered

Safety Factor: MBL equals 6 x WLL

Standard: Meets performance requirements of US Fed Spec RR-C-271, Grade A

Finish: Hot dipped galvanised

Certificate: As standard an EC declaration of conformity is supplied,

also upon request a basic raw material cert, manufacturer test cert,

and inspection cert

	WLL	dia bow	dia pin	dia eye	width eye	width inside	length inside	length	length bolt	width	product code	weight each
		а	b	С	d	е	f	g	h	i		
	tons	mm	mm	mm	mm	mm	mm	mm	mm	mm		kg
	2	13.5	16	34	13	22	43	81	57.5	22	13801	0.32
	3.25	16	19	40	16	27	51	97	71	27	13802	0.58
	4.75	19	22	46	19	31	59	112	82	32	13803	0.92
	6.5	22	25	52	22	36	73	134	93	32	13804	1.33
	8.5	25	28	59	25	43	85	154	108	36	13805	2.03
	9.5	28	32	66	28	47	90	167	120	41	13806	2.88
-	12	32	35	72	32	51	94	180	137	50	13807	3.96
	13.5	35	38	80	35	57	115	209	149	50	13808	5.24
	17	38	42	88	38	60	127	230	164	60	13809	6.80
-	25	45	50	103	45	74	149	271	192	60	13810	11.22

