


Green Pin® ROV Release Polar Shackles P-5365

with locking clamp



- Material:** Body and pin alloy steel, Grade 8, quenched and tempered
- Safety Factor:** MBL equals 8 x WLL for shackles with WLL 17t and 25t
- Safety Factor:** MBL equals 6 x WLL for shackles with WLL 55t and 85t
- Finish:** Body painted white, pin painted green (120t shackle is hot dipped galvanised)
- Temp Range:** Minus 40°C up to 200°C
- Certificate:** As standard an EC declaration of conformity is supplied, also upon request a manufacturer test cert, works cert, and inspection cert
- Note:** It is up to the user to attach the locking clamp with wire ropes, loops and/or monkey's fists. We supply the shackle body, pin and locking clamp with spring pin.

working load limit	bow	diameter		width		inside length	width bow	length	length bolt	width	width locking clamp	product code	weight each
		eye	pin	eye	inside								
tons	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm		kg
6.5	22	25	52	22	36	83	58	160	144	102	44	13201A	1.77
9.5	28	32	66	28	47	108	75	200	177	131	48	13202A	3.66
12	32	35	72	32	51	115	83	215	188	147	48	13203A	4.91
17	38	42	88	38	60	146	99	250	217	175	48	13204A	8.19
25	45	50	103	45	74	178	126	300	250	216	48	13205A	14.22
35	50	57	111	50	83	197	138	331	269	238	48	13206A	19.85
55	65	70	145	65	105	260	180	433	330	310	48	13207A	39.59
85	75	83	162	73	127	329	190	527	380	340	48	13208A	62.00
120	95	95	208	91	147	400	238	647	440	428	60	13209A	110.00
150	105	108	238	102	169	410	275	688	490	485	60	13210A	160.00
200	120	130	279	113	179	513	290	838	520	530	60	13211A	235.00
250	130	140	299	118	205	554	305	904	560	565	60	13212A	285.00

