

Collared Eyebolts - Quality Range

metric coarse thread

- Material:** BS970-080A27 hardened and tempered
Safety Factor: MBL equals 5 x SWL
Standard: BS4278 - table 1 - 1984
Finish: Self colour
Certificate: This product is supplied with an EC declaration of conformity, upon request a certificate of basic raw material
Note: Electro galvanised (zinc plated) also available - prices on request

safe working load	diameter thread	diameter base	diameter eye outside	diameter eye inside	thickness collar	height	thread length	product code	weight each
tonnes	a mm	b mm	c mm	e mm	f mm	g mm	h mm		kg
0.10	6	22	33	15	7	36	18	20001V	0.06
0.15	8	22	33	15	7	36	18	20002V	0.06
0.25	10	22	33	15	7	36	18	20003V	0.06
0.40	12	22	33	15	7	36	18	20004V	0.06
0.50	14	29	44	20	10	48	23	20005V	0.15
0.80	16	29	44	20	10	48	23	20006V	0.15
1.00	18	36	52	24	12	58	28	20007V	0.27
1.60	20	40	59	27	14	65	32	20008V	0.38
1.60	22	45	64	30	14	73	35	20009V	0.54
2.50	24	52	77	35	17	84	40	20010V	0.85
2.50	27	58	85	39	20	94	46	20011V	1.13
4.00	30	65	96	44	22	106	51	20012V	1.62
4.00	33	72	106	48	24	117	56	20013V	2.37
6.30	36	81	118	54	27	131	63	20014V	3.12
6.30	39	81	118	54	27	131	63	20015A	3.12
8.00	42	101	148	68	34	164	79	20016A	6.45
8.00	45	101	148	68	34	164	79	20017A	6.45
10.00	48	101	148	68	34	164	79	20018A	6.51
12.50	52	115	168	76	38	186	89	20019A	9.58
16.00	56	128	188	86	43	208	100	20020A	12.99
20.00	64	144	212	96	48	234	112	20021A	18.20

sizes marked * are additional and proportional to the specification

