

Green Pin® Turnbuckles Eye - Eye G-6311

drop forged

Material: Drop forged high tensile steel SAE 1035 or 1045
Safety Factor: MBL equals 5 x SWL
Standard: Generally to ASTM F1145-92
 Formerly U.S. Federal Specification FF-T-791b
Finish: Hot dipped galvanised
Certificate: As standard an EC declaration of conformity is supplied, also upon request a manufacturer test cert, works cert and inspection cert



diameter thread	take up	length closed position	length open position	dia eye	width inside eye	length inside eye	length closed position	working load limit	product code	weight each
a inches	inches	b mm	c mm	d mm	e mm	f mm	g mm	tons		kg
3/8	6	292	428	10	13	29	49	0.54	60001V	0.47
1/2	6	325	455	12	18	36	58	1.00	60002V	0.84
1/2	9	400	607	12	18	36	57	1.00	60003V	1.05
1/2	12	476	760	12	18	36	57	1.00	60004V	1.26
5/8	6	381	503	14	21	44	79	1.59	60005V	1.35
5/8	9	455	655	14	21	44	78	1.59	60006V	1.60
5/8	12	531	808	14	21	44	78	1.59	60007V	1.92
3/4	6	414	532	17	25	54	90	2.36	60009V	2.03
3/4	9	488	684	17	25	54	89	2.36	60010V	2.49
3/4	12	564	837	17	25	54	89	2.36	60011V	2.65
3/4	18	717	1142	17	25	54	89	2.36	60012V	3.06
7/8	12	601	869	20	32	61	100	3.25	60013V	3.98
7/8	18	754	1174	20	32	61	101	3.25	60014V	5.12
1	6	497	604	24	36	75	118	4.54	60015V	4.35
1	12	647	909	24	36	75	117	4.54	60016V	5.92
1	18	800	1214	24	36	75	117	4.54	60017V	7.17
1	24	950	1517	24	36	75	116	4.54	60018V	7.52
1.1/4	12	711	984	30	46	90	145	6.90	60019V	9.80
1.1/4	18	861	1286	30	46	90	144	6.90	60020V	11.31
1.1/4	24	1014	1590	30	46	90	144	6.90	60021V	12.10
1.1/2	12	756	1023	32	54	105	156	9.71	60022V	14.20
1.1/2	18	916	1335	32	54	105	160	9.71	60023V	16.50
1.1/2	24	1065	1635	32	54	105	158	9.71	60024V	17.10
1.3/4	18	1019	1396	38	60	119	197	12.70	60025V	23.10
1.3/4	24	1171	1701	38	69	119	196	12.70	60026V	26.30
2	24	1264	1783	46	69	147	231	16.80	60027V	40.70
2.1/2	24	1429	1965	51	80	165	274	27.20	60028V	64.00
2.3/4	24	1503	2038	57	84	178	311	34.00	60029V	88.00

