

Dee Shackles

with screw collar pin



Material:	Bow and pin high tensile steel, Grade 4
Safety Factor:	MBL equals 4 x WLL
Standard:	Generally to DIN 82101 type A
Finish:	Hot dipped galvanised
Certificate:	As standard an EC declaration of conformity is supplied
Note:	Self colour also available - prices on request

working load limit	diameter bow	diameter pin	diameter eye	width inside	length inside	product code	weight each
tons	a mm	b mm	c mm	d mm	e mm		kg
0.10	5	5	10	7	16	15301	0.02
0.16	6	6	12	8	18	15302	0.03
0.25	8	8	16	11	24	15303	0.05
0.40	10	10	20	14	30	15304	0.10
0.60	12	12	24	17	36	15305	0.18
1.00	13	16	32	21	49	15306	0.30
1.60	16	20	40	27	61	15307	0.57
2.00	20	22	44	30	67	15308	0.98
2.50	22	24	48	33	73	15309	1.30
3.00	25	27	54	38	84	15310	1.85
4.00	28	30	60	42	91	15311	2.53
5.00	32	36	72	47	111	15312	4.00
6.00	36	39	78	53	120	15313	5.30
8.00	41	45	90	60	140	15314	7.90
10.00	44	48	96	66	147	15315	10.00
12.50	49	52	104	73	158	15316	13.50
16.00	55	60	120	81	185	15317	19.20
20.00	61	68	136	90	211	15318	28.00
25.00	67	72	144	100	221	15319	34.00

