

Excel® Rotating hoist ring, grade 8



- Material:** Alloy steel, grade 8, quenched and tempered
Safety Factor: MBL equals 5 x SWL
Finish: Painted red
Temp Range: up to 250°C
Certificate: This product is supplied with an EC declaration of conformity, also upon request a 3.1 certificate
Note: WLL indicated hereunder are given in the worst conditions of use, i.e. 90°
Note: UNC threads available - prices on request

WLL	thread	inner width	inner length	dia	length	base	outer width	base dia	base dia	inner length	product code	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm		kg
0.40	M8 x 1.25	35	41	13	18	35	68	34	38	43	29801	0.43
0.70	M10 x 1.5	35	39	13	18	37	68	34	38	43	29802	0.44
1.00	M12 x 1.75	35	36	13	22	39	68	34	38	43	29803	0.46
1.30	M14 x 2.0	35	35	13	22	42	68	34	38	43	29804	0.47
1.60	M16 x 2.0	35	42	13	22	43	68	34	38	52	29805	0.52
2.00	M18 x 2.5	35	40	13	28	45	68	34	38	52	29806	0.54
2.50	M20 x 2.5	35	38	13	32	47	68	34	38	52	29807	0.59
3.00	M22 x 2.5	53	57	20	33	69	105	49	56	71	29808	1.88
4.00	M24 x 3.0	53	55	20	33	71	105	49	56	71	29809	1.93
5.00	M27 x 3.0	53	61	20	36	65	105	49	56	71	29810	1.96
6.30	M30 x 3.5	53	61	20	45	65	105	49	56	71	29811	2.03
7.00	M33 x 3.5	71	87	30	50	83	146	68	77	98	29812	5.28
10.00	M36 x 4.0	71	87	30	54	84	146	68	77	98	29813	5.35
10.00	M39 x 4.0	71	87	30	58	84	146	68	77	98	29814	4.81
12.50	M42 x 4.5	71	87	30	63	84	146	68	77	98	29815	5.56

