

# Green Pin® Sockets G-6422

## open spelter socket with safety bolt

**Material:** High tensile steel  
**Finish:** Hot dipped galvanised  
**Temp Range:** Minus 20°C up to 200°C  
**Certificate:** This product is supplied with an EC declaration of conformity upon request a proof load certificate

No.	minimum breaking load	diameter wire rope	length	width	width inside	dia pin	length inside	opening	product code	weight each
	tons	mm	a mm	b mm	c mm	d mm	e mm	f mm		kg
196	8	6 - 7	109	62	19	16	30	8.5	56501	0.4
197	12	8 - 10	124	75	21	21	34	12	56502	0.8
198	20	11 - 13	143	109	26	25	37	15	56503	1.0
199	25	14 - 16	172	133	33	30	49	18	56504	1.8
100	40	18 - 19	205	145	38	35	58	21	56505	3.0
104	55	20 - 22	235	161	44	41	68	24	56506	4.6
108	75	23 - 26	275	189	51	50	75	28	56507	8.0
111	90	27 - 30	306	208	57	57	85	32	56508	11.0
115	125	31 - 36	338	226	63	63	95	38	56509	16.0
118	150	37 - 39	394	246	76	70	127	41	56510	23.0
120	170	40 - 42	418	256	76	77	127	44	56511	27.0

