

Excel® Eyebolt, grade 8



- Material:** Alloy steel, grade 8, quenched and tempered
Safety Factor: MBL equals 5 x SWL
Finish: Painted red
Certificate: This product is supplied with an EC declaration of conformity, also upon request a 3.1 certificate
Note: UNC and BSW threads available - prices on request

WLL	thread dia	dia base	outer eye dia	inner eye dia	length	base dia	dia	MBL	product code	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	t		kg
0.20	M6 x 1.0	20	34	20	20	17	7	1	29701	0.05
0.40	M8 x 1.25	20	34	20	24	17	7	2	29702	0.05
0.70	M10 x 1.5	20	38	22	30	19	8	3.5	29703	0.07
1.00	M12 x 1.75	25	47	26	36	23	10	5	29704	0.13
1.20	M14 x 2.0	30	57	29	40	28	14	6	29705	0.24
1.50	M16 x 2.0	36	65	35	55	30	14	7.5	29706	0.36
2.00	M18 x 2.5	36	65	35	54	30	14	10	29707	0.38
2.50	M20 x 2.5	40	73	39	59	34	16	12.5	29708	0.55
3.00	M22 x 2.5	42	82	44	64	38	19	15	29709	0.73
4.00	M24 x 3.0	55	95	54	84	40	20	20	29710	1.08
5.00	M27 x 3.0	55	95	54	84	42	20	25	29711	1.18
6.00	M30 x 3.5	60	108	59	100	49	24	30	29712	1.87
7.00	M33 x 3.5	60	108	59	100	49	24	35	29713	1.99
8.00	M36 x 4.0	65	118	67	118	45	25	40	29714	2.44
9.00	M39 x 4.0	65	118	67	118	45	25	45	29715	2.58
10.00	M42 x 4.5	70	139	79	135	56	31	50	29716	3.97
15.00	M45 x 4.5	70	139	79	135	56	31	75	29717	4.23
18.00	M48 x 5.0	95	181	97	150	68	43	90	29718	8.33
20.00	M52 x 5.0	95	181	97	150	68	43	100	29719	8.80
25.00	M56 x 5.5	95	181	97	150	68	43	125	29720	9.00
30.00	M60 x 5.5	95	181	97	150	68	43	150	29721	9.50
36.00	M64 x 6.0	95	181	97	150	68	43	180	29722	9.75

