


# Dee Shackles

## with safety bolt



<b>Material:</b>	Bow and pin high tensile steel, Grade 4
<b>Safety Factor:</b>	MBL equals 4 x WLL
<b>Standard:</b>	Generally to DIN 82101 type C
<b>Finish:</b>	Hot dipped galvanised
<b>Certificate:</b>	As standard an EC declaration of conformity is supplied
<b>Note:</b>	Self colour also available - prices on request

working load limit	diameter bow	diameter pin	diameter eye	width inside	length inside	product code	weight each
tons	a mm	b mm	c mm	d mm	e mm		kg
0.40	10	10	20	14	30	15601	0.11
0.60	12	12	24	17	36	15602	0.20
1.00	13	16	32	21	49	15603	0.37
1.60	16	20	40	27	61	15604	0.69
2.00	20	22	44	30	67	15605	1.13
2.50	22	24	48	33	73	15606	1.50
3.00	25	27	54	38	84	15607	2.15
4.00	28	30	60	42	91	15608	2.93
5.00	32	36	72	47	111	15609	4.70
6.00	36	39	78	53	120	15610	6.33
8.00	41	45	90	60	140	15611	8.50
10.00	44	48	96	66	147	15612	10.80
12.00	49	52	104	73	158	15613	14.40
16.00	55	60	120	81	185	15614	20.50
20.00	61	68	136	90	211	15615	29.50
25.00	67	72	144	100	221	15616	36.00

