

Green Pin® Trawling Bow Shackles G-4164

with square headed screw pin

Material: Bow and pin high tensile steel, Grade 6, quenched and tempered

Safety Factor: MBL equals 6 x WLL

Standard: Meets performance requirements of US Fed Spec RR-C-271, Grade A

Finish: Hot dipped galvanised

Certificate: As standard an EC declaration of conformity is supplied,

also upon request a basic raw material cert, manufacturer test cert,

and inspection cert

V	WLL	dia bow	dia pin	dia eye	width eye	width inside	length inside	width bow	length	length bolt	width	bolt head	product code	weight each
		а	b	С	d	e	f	g	h	i	j	k		
t	ons	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm		kg
	2	13.5	16	34	13	22	51	32	89	58	58	22	13901	0.34
3	3.25	16	19	40	16	27	64	43	110	71	75	27	13902	0.63
4	1.75	19	22	46	19	31	76	51	129	82	89	32	13903	1.00
	6.5	22	25	52	22	36	83	58	144	93	102	32	13904	1.44
	8.5	25	28	59	25	43	95	68	164	108	118	36	13905	2.21
	9.5	28	32	66	28	47	108	75	185	120	131	41	13906	3.18
	12	32	35	72	32	51	115	83	201	137	147	50	13907	4.32
1	L3.5	35	38	80	35	57	133	92	227	149	162	50	13908	5.67
	17	38	42	88	38	60	146	99	249	164	175	60	13909	7.36
	25	45	50	103	45	74	178	126	300	192	216	60	13910	12.38

