

Green Pin® Turnbuckles Jaw - Jaw G-6313

drop forged, with cotter pin

Material: Drop forged high tensile steel SAE 1035 or 1045
Safety Factor: MBL equals 5 x SWL
Standard: Generally to ASTM F1145-92
 Formerly U.S. Federal Specification FF-T-791b
Finish: Hot dipped galvanised
Certificate: As standard an EC declaration of conformity is supplied, also upon request a manufacturer test cert, works cert and inspection cert



dia thread	take up	length closed position	length open position	opening jaw	length inside	dia pin	thickness jaw eye	dia jaw eye	WLL	product code	weight each
a	b	c	d	e	f	g	h	tons		kg	
3/4	6	368	487	24	38	16	16	41	2.36	61109X	2.68
3/4	9	442	639	24	38	16	16	41	2.36	61110X	3.03
3/4	12	518	791	24	38	16	16	41	2.36	61111X	3.29
3/4	18	671	1095	24	38	16	16	41	2.36	61112X	3.65
7/8	12	559	825	27	42	19	19	48	3.27	61113X	4.90
7/8	18	712	1131	27	42	19	19	48	3.27	61114X	5.90
1	6	447	555	30	50	22	20	55	4.54	61115X	5.21
1	12	598	859	30	50	22	20	55	4.54	61116X	6.96
1	18	750	1164	30	50	22	20	55	4.54	61117X	8.40
1	24	902	1469	30	50	22	20	55	4.54	61118X	8.90
1.1/4	12	641	916	44	71	29	26	68	6.90	61119X	11.90
1.1/4	18	793	1218	44	71	29	26	68	6.90	61120X	13.60
1.1/4	24	961	1538	44	71	29	26	68	6.90	61121X	14.20
1.1/2	12	675	941	52	71	35	28	80	9.71	61122X	16.90
1.1/2	18	825	1244	52	71	35	28	80	9.71	61123X	19.30
1.1/2	24	980	1550	52	71	35	28	80	9.71	61124X	20.70
1.3/4	18	933	1310	59	86	42	33	90	12.70	61125X	25.00
1.3/4	24	1084	1614	59	86	42	33	90	12.70	61126X	28.70
2	24	1153	1672	63	93	51	41	108	16.80	61127X	45.40
2.1/2	24	1254	1830	75	114	57	41	143	27.20	61128X	88.00
2.3/4	24	1305	1878	90	110	70	41	158	34.00	61129X	98.00

