

Dee Shackles

with counter sunk screw pin

- Material:** Bow and pin high tensile steel, Grade 4
Safety Factor: MBL equals 4 x WLL
Standard: Generally to DIN 82101 type B
Finish: Hot dipped galvanised
Certificate: As standard an EC declaration of conformity is supplied
Note: Self colour also available - prices on request

| working load limit | diameter | | diameter eye | width inside | length inside | product code | weight each |
|--------------------------|----------|---------|-----------------|-----------------|------------------|-----------------|----------------|
| | bow | pin | | | | | |
| tons | a mm | b mm | c mm | d mm | e mm | | kg |
| 0.40 | 10 | 10 | 20 | 14 | 30 | 15401 | 0.09 |
| 0.60 | 12 | 12 | 24 | 17 | 36 | 15402 | 0.17 |
| 1.00 | 13 | 16 | 32 | 21 | 49 | 15403 | 0.29 |
| 1.60 | 16 | 20 | 40 | 27 | 61 | 15404 | 0.54 |
| 2.00 | 20 | 22 | 44 | 30 | 67 | 15405 | 0.95 |
| 2.50 | 22 | 24 | 48 | 33 | 73 | 15406 | 1.23 |
| 3.00 | 25 | 27 | 54 | 38 | 83.5 | 15407 | 1.80 |
| 4.00 | 28 | 30 | 60 | 42 | 91 | 15408 | 2.60 |
| 5.00 | 32 | 36 | 72 | 47 | 111 | 15409 | 3.80 |

