

Eyebolts without collar

metric coarse thread

Material: High tensile steel
Safety Factor: MBL equals 8 x SWL
Standard: B.S. 5655 - Part 8 -1983
Finish: Self colour
Certificate: This product is supplied with an EC declaration of conformity



| working load limit | diameter thread | diameter rope | diameter eye | diameter eye inside | nominal length | length thread | product code | weight each |
|--------------------|-----------------|---------------|--------------|---------------------|----------------|---------------|--------------|-------------|
| tonnes | a mm | mm | b mm | c mm | f mm | g mm | | kg |
| 0.20 | 10 | 6.5 | 10 | 15 | 150 | 115 | 24401 | 0.16 |
| | | | | | 300 | 230 | 24402 | 0.20 |
| 0.31 | 12 | 8 | 12 | 15 | 150 | 115 | 24403 | 0.30 |
| | | | | | 300 | 230 | 24404 | 0.40 |
| 0.60 | 16 | 11 | 17 | 21 | 300 | 230 | 24405 | 0.80 |
| | | | | | 450 | 345 | 24406 | 0.93 |
| 0.83 | 20 | 13 | 20 | 24 | 600 | 460 | 24407 | 1.14 |
| | | | | | 450 | 345 | 24408 | 1.47 |
| 1.27 | 24 | 16 | 24 | 27 | 600 | 460 | 24409 | 1.77 |
| | | | | | 750 | 575 | 24410 | 2.10 |
| 1.79 | 30 | 19 | 29 | 34 | 450 | 345 | 24411 | 2.87 |
| | | | | | 600 | 460 | 24412 | 3.40 |
| 1.79 | 30 | 19 | 29 | 34 | 750 | 575 | 24413 | 4.00 |
| | | | | | 600 | 460 | 24414 | 6.50 |
| | | | | | 750 | 575 | 24415 | 6.90 |

