

Green Pin® Turnbuckles Jaw - Jaw G-6323

drop forged, with safety bolt

Material: Drop forged high tensile steel SAE 1035 or 1045
Safety Factor: MBL equals 5 x SWL
Standard: Generally to ASTM F1145-92
 Formerly U.S. Federal Specification FF-T-791b

Finish: Hot dipped galvanised

Certificate: As standard an EC declaration of conformity is supplied, also upon request a manufacturer test cert, works cert and inspection cert



| dia thread | take up | length closed position | length open position | opening jaw | length inside | dia pin | thickness jaw eye | dia jaw eye | WLL | product code | weight each |
|------------|---------|------------------------|----------------------|-------------|---------------|---------|-------------------|-------------|-------|--------------|-------------|
| a | b | c | d | e | f | g | h | tons | | kg | |
| inches | inches | mm | mm | mm | mm | mm | mm | | | | |
| 3/8 | 6 | 273 | 409 | 12 | 21 | 8 | 9 | 21 | 0.54 | 61101V | 0.57 |
| 1/2 | 6 | 305 | 435 | 16 | 26 | 10 | 11 | 26 | 1.00 | 61102V | 0.96 |
| 1/2 | 9 | 380 | 587 | 16 | 26 | 10 | 11 | 26 | 1.00 | 61103V | 1.18 |
| 1/2 | 12 | 455 | 739 | 16 | 26 | 10 | 11 | 26 | 1.00 | 61104V | 1.50 |
| 5/8 | 6 | 346 | 469 | 18 | 32 | 13 | 14 | 33 | 1.59 | 61105V | 1.84 |
| 5/8 | 9 | 421 | 622 | 18 | 32 | 13 | 14 | 33 | 1.59 | 61106V | 2.12 |
| 5/8 | 12 | 496 | 773 | 18 | 32 | 13 | 14 | 33 | 1.59 | 61107V | 2.56 |
| 3/4 | 6 | 368 | 487 | 24 | 38 | 16 | 16 | 41 | 2.36 | 61109V | 2.68 |
| 3/4 | 9 | 442 | 639 | 24 | 38 | 16 | 16 | 41 | 2.36 | 61110V | 3.03 |
| 3/4 | 12 | 518 | 791 | 24 | 38 | 16 | 16 | 41 | 2.36 | 61111V | 3.29 |
| 3/4 | 18 | 671 | 1095 | 24 | 38 | 16 | 16 | 41 | 2.36 | 61112V | 3.65 |
| 7/8 | 12 | 559 | 825 | 27 | 42 | 19 | 19 | 48 | 3.27 | 61113V | 4.90 |
| 7/8 | 18 | 712 | 1131 | 27 | 44 | 19 | 19 | 48 | 3.27 | 61114V | 5.95 |
| 1 | 6 | 447 | 555 | 30 | 50 | 22 | 20 | 55 | 4.54 | 61115V | 5.21 |
| 1 | 12 | 598 | 859 | 30 | 50 | 22 | 20 | 55 | 4.54 | 61116V | 6.96 |
| 1 | 18 | 750 | 1164 | 30 | 50 | 22 | 20 | 55 | 4.54 | 61117V | 8.40 |
| 1 | 24 | 902 | 1469 | 30 | 50 | 22 | 20 | 55 | 4.54 | 61118V | 8.90 |
| 1.1/4 | 12 | 641 | 916 | 44 | 71 | 28 | 26 | 68 | 6.90 | 61119V | 11.90 |
| 1.1/4 | 18 | 793 | 1218 | 44 | 71 | 28 | 26 | 68 | 6.90 | 61120V | 13.60 |
| 1.1/4 | 24 | 961 | 1538 | 44 | 71 | 28 | 26 | 68 | 6.90 | 61121V | 14.20 |
| 1.1/2 | 12 | 675 | 941 | 52 | 71 | 35 | 28 | 80 | 9.71 | 61122V | 16.90 |
| 1.1/2 | 18 | 825 | 1244 | 52 | 71 | 35 | 28 | 80 | 9.71 | 61123V | 19.30 |
| 1.1/2 | 24 | 980 | 1550 | 52 | 71 | 35 | 28 | 80 | 9.71 | 61124V | 20.70 |
| 1.3/4 | 18 | 933 | 1310 | 59 | 86 | 42 | 33 | 90 | 12.70 | 61125V | 25.00 |
| 1.3/4 | 24 | 1084 | 1614 | 59 | 86 | 42 | 33 | 90 | 12.70 | 61126V | 28.70 |
| 2 | 24 | 1153 | 1672 | 63 | 93 | 50 | 41 | 108 | 16.80 | 61127V | 45.40 |
| 2.1/2 | 24 | 1254 | 1830 | 75 | 114 | 57 | 41 | 143 | 27.20 | 61128V | 88.00 |
| 2.3/4 | 24 | 1305 | 1878 | 90 | 110 | 70 | 41 | 158 | 34.00 | 61129V | 98.00 |

