

Green Pin® Sockets G-6413

open wedge type

Material: High tensile steel
Standard: Generally to EN13411-6
Finish: Hot dipped galvanised
Temp Range: Minus 20°C up to 200°C
Certificate: This product is supplied with an EC declaration of conformity upon request a proof load certificate

No.	MBL	dia wire rope	length	length to centre pin	width	width inside	pin dia	side plate t'ness	eye dia	product code	weight each
	tons	mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm		kg
0.25	8	7 - 8	128	110	51	18	16	9	36	50001	0.80
0.5	12	9 - 10	165	142	62	20	21	11	46	50002	1.50
1	20	11 - 13	175	146	66	25	25	12	57	50003	2.40
2	25	14 - 16	211	176	82	31	30	15	70	50004	4.00
3	40	18 - 19	252	212	95	38	35	16	80	50005	7.00
4	55	20 - 22	288	240	110	44	41	19	95	50006	11.00
5	75	24 - 26	329	274	130	51	51	22	110	50007	16.00
6	90	27 - 29	375	310	145	57	57	25	130	50008	21.00
7	110	30 - 32	423	350	155	63	64	28	146	50009	30.00
8	125	34 - 36	474	400	163	69	64	28	148	50010	37.00
9	150	37 - 39	527	450	178	76	70	30	153	50011	51.00
10	170	40 - 42	580	500	187	76	76	33	160	50012	64.00
11	225	43 - 48	650	550	226	89	89	39	186	50013	96.00
12	280	49 - 52	745	640	257	101	95	46	194	50014	130.00
13	360	54 - 58	785	660	275	114	108	54	230	50015	180.00
14	425	60 - 68	970	835	300	127	121	60	250	50016	275.00
15	460	72 - 76	1150	1000	355	146	133	76	270	50017	440.00
16	625	81 - 86	1252	1100	375	159	140	79	300	50018	510.00

