

# Green Pin® Polar Turnbuckles Jaw - Jaw G-6333

with safety bolt



**Material:** Drop forged alloy steel grade 8, quenched and tempered  
**Safety Factor:** MBL equals 5 x SWL  
**Standard:** Generally to ASTM F1145-92  
 Formerly U.S. Federal Specification FF-T-791b  
**Finish:** Hot dipped galvanised  
**Temp Range:** Minus 40°C up to 200°C  
**Certificate:** As standard an EC declaration of conformity is supplied,  
 also upon request a manufacturer test cert, works cert, and inspection cert

dia thread	take up	length closed position	length open position	opening jaw	length inside	dia pin	thickness jaw	diameter eye	working load limit	product code	weight each
a	b	c	d	e	f	g	h	tons	kg		
inches	inches	mm	mm	mm	mm	mm	mm	mm			
1/2	12	455	739	16	26	10	11	26	1.00	61501	1.50
5/8	12	496	773	18	32	13	14	33	1.59	61502	2.56
3/4	18	671	1095	24	38	16	16	41	2.36	61503	3.65
7/8	18	712	1131	27	42	19	19	48	3.27	61504	5.95
1	18	750	1164	30	50	22	20	55	4.54	61505	8.40
1.1/4	18	793	1218	44	71	29	26	68	6.90	61506	13.60
1.1/2	18	825	1244	52	71	35	28	80	9.71	61507	19.30
1.3/4	18	933	1310	59	86	42	33	90	12.70	61508	25.00

