

# Galvanised Turnbuckles Jaw - Jaw

## drop forged

**Material:** Drop forged high tensile steel SAE 1035 or 1045  
**Safety Factor:** MBL equals 5 x SWL  
**Standard:** Generally to ASTM F1145-92  
 Formerly U.S. Federal Specification FF-T-791b  
**Finish:** Hot dipped galvanised  
**Certificate:** This product is supplied with an EC declaration of conformity



dia thread	take up	length closed position	length open position	opening jaw	length inside	dia pin	thickness jaw eye	dia jaw eye	WLL	product code	weight each
a	b	c	d	e	f	g	h	tons		kg	
inches	inches	mm	mm	mm	mm	mm	mm				
3/8	6	302	454	13	22	8	8	21	0.54	61101	0.37
1/2	6	338	490	16	26	9.5	10	25	1.00	61102	0.73
1/2	9	414	642	16	26	9.5	10	25	1.00	61103	0.79
1/2	12	490	795	16	26	9.5	10	25	1.00	61104	0.96
5/8	6	394	546	18	33	13	13	33	1.59	61105	1.37
5/8	9	470	698	18	33	13	13	33	1.59	61106	1.41
5/8	12	546	851	18	33	13	13	33	1.59	61107	1.53
5/8	18	701	1150	18	33	13	13	33	1.59	61108	1.86
3/4	6	432	584	23	38	15.5	16	41	2.36	61109	1.86
3/4	9	508	736	23	38	15.5	16	41	2.36	61110	2.31
3/4	12	584	889	23	38	15.5	16	41	2.36	61111	2.56
3/4	18	737	1194	23	38	15.5	16	41	2.36	61112	3.11
7/8	12	625	854	27	44	19	18	48	3.27	61113	3.71
7/8	18	778	1121	27	44	19	18	48	3.27	61114	4.14
1	6	524	676	30	52	22	20	54	4.54	61115	4.29
1	12	676	981	30	52	22	20	54	4.54	61116	5.07
1	18	829	1286	30	52	22	20	54	4.54	61117	6.62
1	24	980	1592	30	52	22	20	54	4.54	61118	7.85
1.1/4	12	760	1055	44	73	29	25	67	6.90	61119	9.48
1.1/4	18	912	1370	44	73	29	25	67	6.90	61120	11.60
1.1/4	24	1064	1665	44	73	29	25	67	6.90	61121	13.00
1.1/2	12	823	1129	52	70	35	27	80	9.71	61122	13.60
1.1/2	18	975	1434	52	70	35	27	80	9.71	61123	14.30
1.1/2	24	1228	1738	52	70	35	27	80	9.71	61124	18.40
1.3/4	18	1060	1533	59	85	41	33	90	12.70	61125	25.00
1.3/4	24	1213	1838	59	85	41	33	90	12.70	61126	28.70
2	24	1315	2011	64	93	41	39	108	16.78	61127	45.40
2.1/2	24	1486	2098	75	114	57	38	143	27.22	61128	73.00
2.3/4	24	1562	2171	89	110	70	42	156	34.02	61129	98.00

