

Long Shank Collared Eyebolts



BSW thread

Material: High tensile steel
Safety Factor: MBL equals 5 x SWL
Finish: Self colour
Certificate: This product is supplied with an EC declaration of conformity
Note: Electro galvanised (zinc plated) also available - prices on request

safe working load	diameter thread	diameter base	diameter eye outside	diameter eye inside	thickness collar	height	thread length	product code	weight each
tonnes	a inch	b inch	c inch	e inch	f inch	g inch	h inch		kg
0.25	3/8	27/32	1.5/16	9/16	9/32	1.3/8	7	21501A	0.18
0.50	1/2	1.1/8	1.5/8	3/4	3/8	1.3/4	7	21502A	0.25
0.90	5/8	1.13/32	2	15/16	15/32	2.1/4	7	21503A	0.44
1.40	3/4	1.11/16	2.7/16	1.1/8	9/16	2.3/4	7	21504A	0.70
2.00	7/8	1.31/32	2.13/16	1.5/16	21/32	2.7/8	7	21505A	1.05
2.75	1	2.1/4	3.1/4	1.1/2	3/4	3.7/16	7	21506A	1.50
3.50	1.1/8	2.13/16	4.1/8	1.7/8	15/16	4.1/2	7	21507A	2.80
4.50	1.1/4	2.13/16	4.1/8	1.7/8	15/16	4.1/2	7	21508A	2.90

*
*

* UNC thread also available upon request

